

PRODUCT INFORMATION



BESFLOC K320AF

DRY ANIONIC FLOCCULANT

Product Description

BESFLOC K320AF is a high molecular weight, low charged anionic flocculant

The product is a free flowing granular powder which is completely water soluble.

Principal Uses

BESFLOC K320AF is usually used as a coagulant aid for sedimentation and dewatering aid for liquid-solids separation processes.

- * Coagulant aid for sedimentation of suspended solids in potable water & industrial water.
- * Dewatering of potable water sludges in the Belt Press, Screw Press and Filter Press - increasing filtration rates, cake solids content and solids capture.

Application and Storage

Recommended solution concentrations ;

Feed Solution : 0.05 ~ 0.1%

Recommended storage periods ;

Granular product in Original Packing : up to 2 years

Unopened paper bags should be stored in a cool, dry place. Partially empty bags should be carefully closed to prevent moisture pick up.

Typical Properties

Physical Form	white granular powder
Particle Size	0.1mm < 95% < 1mm
Ionic Charge	High Anionic
Salt Viscosity @25 °C 0.5% in 4% NaCl Solution	130 ~ 180 cps
pH of 0.1% solution	6.0 ~ 8.0

BESFLOC K320AF

DRY ANIONIC FLOCCULANT

Shipping and Handling

Besfloc is supplied in 10kg paper bag with inner polyethylene bag. **BESFLOC** has a low order of toxicity and no special precautions are necessary in handling. It is needed to **dissolve more than 1 hour** to make up feeding solution. Product solutions should be made up and diluted in stainless steel, FRP or plastic coated vessels. Make-up temperatures should be between 15 - 30°C (60 - 85°F). The use of allminum, mild steel and copper-containing alloys for solution storage, pumps or associated piping should be avoided.

Health and Safety Information

BESFLOC exhibits a very low order of toxicity and does not present any abnormal problems in its handling or general use. Nevertheless, precaution should be taken to prevent inhalation, ingestion or contact with the skin or eyes. Observing basic industrial hygiene precautions, should prevent any health or safety hazards.

* **Full details on Health and Safety aspects are available on request.**

Dry polymer spills should be left dry and swept up immediately.

Note : Spills of dilute solutions can be extremely slippery.

Warranty

The above information is based on data KOLON LIFE SCIENCE., Inc. believes reliable and is supplied for informational purpose only. KOLON disclaims any liability for damage or injury which results from the use of the above data and nothing contained therein.

User should undertake sufficient verification and testing to determine suitable flocculating grade for their own particular purpose.

NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS MADE.

Trade name

BESFLOC is the registered trade name of KOLON LIFE SCIENCE, INC..

Please refer hereunder for further details.



KOLON LIFE SCIENCE, INC.

Water Solution Business Team

Business Contact : Phone 82-2-3677-3649 Fax 82-2-3677-3557

Homepage : <http://www.kolonls.com>
